

Michael Lawrence Beauchamp
651-B Minna Street, San Francisco, CA. 94103 (415)756-7331 Jul. 2,
2003

METHOD FOR PRODUCING LATERAL EJECTION APPARATUS FOR HELICOPTER OR PLANE

Inventor: Michael Lawrence Beauchamp, California, United States

Appl. No.:

Date Filed:

Int. Cl......B64D 25/10; B61G 5/02; B64D 25/00; B60R
21/22; B60N 5/00; B61D 1/00; B64D 11/06; B64C 1/32; B64C 1/00;
B64D 25/12; B64D 11/00; B64D 17/72; B64C 1/14; B64C 27/82
U.S. Cl......244/122 A; 244/122; 244/122 AC; 244/122
AD; 244/122AG; 244/122AF; 244/141; 244/121; 244/129.5; 244/118.6

Field of Search......244/122 A. AC. AD. AG. AF,
R; 244/118.6; 244/121; 244-122; 244/120; 244-129; 244/132; 244/137;
244/137 P; 244/8; 244/138 R; 244/129.5; 244/129.1; 244/1 R; 244/150;
244/152

References Cited

U.S. PATENT DOCUMENTS

6,299,103 10/2001 Shope et al.....244/122 A
4,303,212 12/1981 Stone et al.....244/122 AD
3,424,409 1/1969 R.M. Stanley.....244-122
4,215,835 8/1980 Wedgewood.....244/122 AG ENG
5,056,739 10/1991 LeVay.....244/122 AG
4,216,928 8/1980 Hooper et al.....244/122 AD
4,765,570 8/1988 Herndon.....244/122
3,623,683 11/1971 Bennett.....244/122
4,667,901 5/1987 Herndon.....244/122 AC
4,706,909 11/1987 Cuevas et al.....244/122 AC
4,480,806 11/1984 Duncan.....244/122 A
3,966,146 6/1976 Roberts.....244/122 A
3,981,465 9/1976 Sinnett et al.....244/122 A
3,158,344 11/1964 C.T. Koochembere.....244-122 A
4,667,904 5/1987 Herndon.....244/122 R
4,645,147 2/1987 Hendricks.....244/137 P
3,863,731 1/1975 McIntyre.....244/141
3,862,731 1/1975 McIntyre.....244/141

4,007,895 2/1977 Payne.....244/138 R
4,813,634 3/1989 Zuck.....244/122 A
3,662,978 5/1972 Hollrock.....244/122 A
4,470,565 9/1984 Zenobi et al.....244/122 A
4,655,416 4/1987 Carnell et al.....244/121
3,670,998 6/1972 Charleville et al.....244/121
4,275,858 6/1981 Bolton et al.....244/121 ENG
Continued on pages (2) and (3).

Other Helicopters with Sliding Doors:

Kaman H-2
HU3, Huskie Seasprite
Kamov Ka-25

ABSTRACT

An aircraft occupancy, here a helicopter with a seat chassis mounted on a set of rails of any type, ideally as I have demonstrated on load bearing triple monorails with one hundred sixty-eight circumventing roller trucks attached to the inner rails, an outer track box movable along the inner tracks, and a monorail supporting track with eighty-four roller trucks. Shown here in a side view with partial delineation of the mesh end cover Any seat chassis attached to the outer track box is ejectable along a lateral trajectory, perpendicular to the horizontal longitudinal axis of an aircraft, and guided out of the path of a failed aircraft during ejection flight by two bottom positioned tail fins slotted within the ejection monorails launcher platform legs. The seat chassis is enabled to eject laterally since a conventional hinged door is operational within a greater sliding door panel which pneumatic rockets at the top and bottom of the sliding door transverse the greater emergency sliding door panel including the interior fixed conventional hinge operational door out of the path of the seat chassis or chassis' attached to the outer track box towards the rear of the aircraft where the sliding greater panel is prevented from recoiling by a common latch catches. Dual airbags for positioning the legs and torso of an occupant for a safe emergency exit ejection are embedded or attached to the structure directly fore of the seat chassis. A second set of airbags, head, neck and chest protector are connected on both sides of the seat chassis, mandatory for safe lateral equal access emergency exit ejection. Three compartments for altitude appropriate parachutes and sensor fuse box for opening said desired chute. Including an interior side mounted blast shield and monorails inner tracks support to which a couple of rocket catapults are fixed by seals at their ignition points, holding the outer track box and seat chassis stationary between the inner tracks and supporting track.

20 Claims, 15 Drawing Figures

